

This Page Is Inserted by IFW Operations  
and is not a part of the Official Record

## **BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

**IMAGES ARE BEST AVAILABLE COPY.**

As rescanning documents *will not* correct images,  
please do not report the images to the  
Image Problem Mailbox.

THIS PAGE BLANK (ISPT0)

# (12) UK Patent Application (19) GB (11) 2 279 571 (13) A

(43) Date of A Publication 11.01.1995

(21) Application No 9312197.8

(22) Date of Filing 14.06.1993

(71) Applicant(s)  
Minnesota Mining and Manufacturing Company  
(Incorporated in USA - Delaware)  
  
PO Box 33427, 3M Center, Saint Paul,  
Minnesota 55144-1000, United States of America

(72) Inventor(s)  
Eduard Marx

(74) Agent and/or Address for Service  
Lloyd Wise, Tregear & Co  
Norman House, 105-109 Strand, LONDON, WC2R 0AE,  
United Kingdom

(51) INT CL<sup>6</sup>  
A61M 11/04 15/00


(52) UK CL (Edition N )  
A5T TBE TEB

(56) Documents Cited  
EP 0186280 A2 WO 92/09323 A1 US 4796614 A  
US 3456644 A

(58) Field of Search  
UK CL (Edition L ) A5T TBE TCR TDC TEB  
INT CL<sup>5</sup> A61M

## (54) Inhaler

(57) A component (2) of an inhaler adapted to be assembled with one or more other components (4) to complete the inhaler, comprises a reservoir of medicament (6) having a dispensing port (10), a housing (8) substantially enveloping the reservoir and retaining means (12) which prevents removal of the reservoir (6) from the housing (8), maintains the dispensing port (10) aligned in a predetermined direction and allows movement of the reservoir (6) within the housing (8).



At least one drawing originally filed was informal and the print reproduced here is taken from a later filed formal copy.

GB 2 279 571 A

Fig. 1





Fig. 2



INHALER

This invention relates to inhalers and in particular to pressurised inhalers.

5 Since the metered dose pressurised inhaler was introduced in the mid-1950's, inhalation has become the most widely used route for delivering bronchodilators, offering a rapid onset of action and a low instance of systemic side effects. More recently, inhalation from a  
10 pressurised inhaler has been a route selected for the administration of other drugs, e.g., ergotamine, which are not primarily concerned with the treatment of a bronchial malady.

The metered dose inhaler is dependent upon the  
15 propulsive force of a propellant system used in its manufacture. The propellant generally comprises a mixture of liquified chlorofluorocarbons (CFC's) which are selected to provide the desired vapour pressure and stability of the formulation. Propellants 11, 12 and 114  
20 are the most widely used propellants in aerosol formulations for inhalation administration. Recently, non-CFC propellant systems have been proposed in view of the adverse effect of CFC's on the ozone layer. The drugs are formulated in the propellant system as a  
25 solution or dispersion, generally in the presence of a surfactant.

The drug/propellant formulation is contained in an aerosol vial equipped with a metered dose valve. The aerosol vial is inserted within an adaptor which  
30 comprises a housing having a mouthpiece or nasal port through which the patient inhales the drug during actuation of the valve. The adaptor may be of the "press and breathe" type which requires the patient to actuate the valve during inhalation or of the "inhalation-  
35 actuated" type which actuates the valve as the patient inhales.

Inhalation activatable dispensers for use with aerosol containers are described in British Patent Specification Nos. 1269554, 1335378, 1392192 and 2061116 and United States Patent Nos. 3,456,644, 3,456,645, 3,456,646, 3,565,070, 3,598,294, 3,814,297, 3,605,738, 3,732,864, 3,636,949, 3,789,843 and 3,187,748 and German Patent No. 3040641.

European Patent No. 147028 discloses an inhalation activatable dispenser for use with an aerosol container in which a latch mechanism releasing vane is pivotally mounted in an air passage between an aerosol outlet valve and a mouthpiece, which latch mechanism cannot be released if force to activate the dispenser is not applied before a patient inhales.

This inhalation device, commercially available from Minnesota Mining and Mining Manufacturing Company under the registered trade mark AUTOHALER, has been received favourably by patients and doctors since it not only overcomes the hand-lung co-ordination problem but it does so at a very low triggering flow-rate (approximately 30 litres/minute) essentially silently, and with a very compact design barely larger than a standard inhaler.

Some of the inhalation activatable inhalers are formed of two main parts, one part which holds the aerosol container and the second part comprising the mouthpiece and nozzle block into which the valve stem of the aerosol container is inserted. It is important that the stem is correctly aligned with the nozzle block when the two parts are assembled otherwise damage and/or failure of the unit may occur. Such assembly may take place not only during manufacture of the inhaler but also during the lifetime of the product since it may be necessary to disassemble the parts for washing.

One problem associated with the use of aerosol containers is that relative movement between the valve stem and aerosol container is required to dispense a dose and in many devices it is not possible to secure the

aerosol container to one part of the device since this would prevent the required movement. Thus, it is desirable to be able to retain an aerosol container in a part of an inhaler which will ensure the correct  
5 alignment of the aerosol container and yet retain the ability for the aerosol container to move sufficiently to operate the valve.

According to the present invention there is provided a component of an inhaler adapted to be assembled with  
10 one or more other components to complete the inhaler, the component comprising a reservoir of medicament having a dispensing port, a housing substantially enveloping the reservoir and retaining means which prevents removal of the reservoir from the housing, maintains the dispensing  
15 port aligned in a predetermined direction and allows movement of the reservoir within the housing.

The invention is particularly useful with aerosol containers which<sup>1</sup> may be accommodated within a cylindrical housing and maintained in place by an annular retaining  
20 means positioned within the mouth of the cylinder with the valve stem protruding thereby preventing removal of the aerosol container and holding the container with the valve stem correctly aligned. The annular retaining means may be adhered in place, may be a force fit within  
25 the housing or have mechanical engaging means. Preferably the retaining means comprises a skirt portion extending along the inner cylindrical wall of the housing.

The component of the invention has the following  
30 advantages:

- i) Guaranteed correct assembly of the device.
- ii) Prevents the substitution of alternative aerosol cans which would not necessarily function properly in the device.
- 35 iii) Allows pre-packaged top assemblies and cans to be marketed.

iv) During cleaning the patient has one less part to handle, simplifying reassembly.

The invention will now be described with reference to the accompanying drawings in which:

Figure 1 represents a section through part of an inhaler showing the retaining means, and

Figure 2 represents a section through an inhaler showing the part of Figure 1.

Figure 1 shows a portion of a component (2) which is assembled with component (4) (Figure 2) to form an inhaler. The inhaler illustrated is inhalation activatable and is of the type disclosed in EP-147028.

An aerosol container (6) is accommodated within the housing (8) of component (2) with the valve stem (10) projecting outwardly from the housing. In order to maintain the alignment of the valve stem (10) in the longitudinal direction, a retaining means (12) is positioned within the housing (8). The retaining means (12) comprises an annular ring (14) which is dimensioned to allow a clearance fit of the valve ferrule (16) but prevent removal of the aerosol container (6) since the aperture (18) has a smaller diameter than the outer diameter of the aerosol container (6). The retaining means (12) is held in place within the housing by a skirt portion (20) which extends along the inner wall of the housing (8). The skirt portion may be a force fit within the housing (8), may be adhered to the inner wall or may have mechanical engaging means, e.g. complimentary projections and recesses (not shown). The retaining means allows limited movement of the aerosol container (6) in the longitudinal direction whilst maintaining the alignment of the valve stem (10).

Referring to Figure 2, the components (2, 4) are combined to form the inhaler. The component (4) comprises a housing (22), a mouthpiece (24) and a nozzle block (26). The component (4) also comprises a breath-



actuated mechanism which has been omitted in the interests of clarity.

5       The components (2, 4) are provided with  
complimentary threads which allows the two components to  
be assembled by rotation. During assembly it is  
essential that the valve stem (10) is located within the  
nozzle block (26). Failure to ensure correct alignment  
could result in the valve stem (10) completely missing  
the nozzle block, rendering the inhaler inoperable, or  
10   could lead to the valve stem or nozzle block being  
damaged by forces generated during assembly of the two  
components (2, 4). The retaining means (12) ensures the  
valve stem (10) is correctly aligned and will be  
introduced into the nozzle block (26) as the two  
15   components (2, 4) are assembled.

CLAIMS

1. A component of an inhaler adapted to be assembled with one or more other components to complete the inhaler, the component comprising a reservoir of  
5 medicament having a dispensing port, a housing substantially enveloping the reservoir and retaining means which prevents removal of the reservoir from the housing, maintains the dispensing port aligned in a predetermined direction and allows movement of the  
10 reservoir within the housing.
2. A component of an inhaler as claimed in Claim 1 in which the reservoir is an aerosol container.
3. A component of an inhaler as claimed in Claim 1 or Claim 2 in which the housing is substantially  
15 cylindrical.
4. A component of an inhaler as claimed in Claim 3 in which the retaining means is annular and fits within the cylindrical housing, the dispensing port projecting through the annular.
- 20 5. A component of an inhaler as claimed in Claim 4 in which the retaining means comprises a skirt extending along the inner wall of the housing.

Patents Act 1977  
Examiner's report to the Comptroller under  
Section 17 (The Search Report)

Application number  
GB 9312197.8

Relevant Technical fields

(i) UK CI (Edition L ) A5T (TBE, TCR, TDC, TEB)

(ii) Int CI (Edition 5 ) A61M

Databases (see over)

(i) UK Patent Office

(ii)

Search Examiner

M SIDDIQUE

Date of Search

27 JULY 1993

Documents considered relevant following a search in respect of claims 1-5

Category (see over)	Identity of document and relevant passages	Relevant to claim(s)
X	EP 0186280 A2 (LANDIS) housing 10, reservoir 24 moved by spring, retaining means 44 etc	1, 3
X	WO 92/09323 A1 (NORTON) housing 5, reservoir 20/25 moved by spring 80, retainer defined by wall cross 10	1-4
A	US 4796614	1
X	US 3456644 (THIEL) Figure 10, 11; retaining means 83, 84	1-3

Category	Identity of document and relevant passages -8-	Relevant to claim.

#### Categories of documents

X: Document indicating lack of novelty or of inventive step.

Y: Document indicating lack of inventive step if combined with one or more other documents of the same category.

A: Document indicating technological background and/or state of the art.

P: Document published on or after the declared priority date but before the filing date of the present application.

E: Patent document published on or after, but with priority date earlier than, the filing date of the present application.

&: Member of the same patent family, corresponding document.

**Databases:** The UK Patent Office database comprises classified collections of GB, EP, WO and US patent specifications as outlined periodically in the Official Journal (Patents). The on-line databases considered for search are also listed periodically in the Official Journal (Patents).